



AREA LIGHTS AL-14 SERIES



TYPE

SPECIFICATIONS

CONSTRUCTION: Cast aluminum or cast brass Oriental Hat; matching extruded aluminum or brass stanchion

LAMP SUPPLIED: 18 watt S-8 #1141; 1200 hours average rating (25w max.)

LAMP OPTIONS: We recommend 10,000 hours average rating Xenon (-X) or Halogen (-H) or 2.2w 50,000 hours average rating OMNI-2 LED

SOCKET: Single contact bayonet, brass nickel plated lamp socket screw shell (Ba15); double contact bayonet base (Ba15d) for 120v., both with 200° C silicone lead wires

WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v. only)

For 25 foot 16/2 fixture lead wire add **-25F** to catalog number.

120v. Standard wiring

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only) 12v. only

MOUNTING: FA-03 black 9" ABS stake, tapped 1/2" NPS

FINISH: Aluminum-Black texture polyester powder coat—optional finishes available
Brass-Unfinished brass—optional finishes available

ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
AL-14-BLT	Cast Aluminum 8" Oriental Hat	18w S8 #1141	4.0 lbs.
AL-14-BRS	Cast Brass 8" Oriental Hat	18w S8 #1141	7.0 lbs.



AL-14-BRS




MOUNTING ACCESSORIES

BEAM/GLARE CONTROL ACCESSORIES

FA-97-14 AL-01 Sprinkler Guard / Glare Shield

-AH Add to catalog # for Adjustable Hub

LIGHT DISTRIBUTIONS AND PHOTOMETRICS



AL-14
Half Spread Photometrics
20 ft. (6.1m) diameter

JOB INFORMATION

Type: _____ Date: _____

Job Name: _____

Cat. No.: _____

Lamp(s): _____

Specifier: _____

Contractor: _____

Notes: _____

FOCUS INDUSTRIES INC.
25301 COMMERCENTRE DRIVE
LAKE FOREST, CA 92630

www.focusindustries.com
sales@focusindustries.com
(949) 830-1350 • FAX (949) 830-3390

Powder Coat Finishes	Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Terra Cotta
Ordering Code	-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-TRC