



# DIRECTIONAL LIGHTS DL-22-SERIES



TYPE

## SPECIFICATIONS

**CONSTRUCTION:** Cast aluminum, brass or 316 Stainless Steel Bullet; matching heavy duty cast aluminum, brass or 316 Stainless Steel adjustable swivel

**LENS:** High impact clear tempered convex glass

**O-RING:** High temperature red silicone

**LAMP SUPPLIED:** 20 watt MR16 FL(BAB) 5000 hours average rating (50w max)

**LAMP OPTIONS:** We recommend 20 watt MR16 ULTRA10,000 hours average rating; 20 watt MR16 TITAN 18,000 hours average rating; 4w ARROW LED 50,000 average rating

**SOCKET:** High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires

**WIRING:** Black 3 foot 18/2 zip cord from base of fixture (12v. only)

For 25 foot 16/2 fixture lead wire add **-25F** to catalog number.

**CONNECTION:** FA-05 Quick Connector (not supplied) from fixture to main cable (1/2, 10/2 or 8/2 only)

**MOUNTING:** FA-03 black 9" ABS stake threaded 1/2" NPS


**FINISH:** Aluminum-Black texture polyester powder coat; optional finishes available. Brass-Unfinished brass; optional finishes available. Stainless Steel - machined finish

## ORDERING INFORMATION


CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
DL-22-BLT	Cast aluminum Bullet	20w MR16 FL(BAB)	2.0 lbs.
DL-22-BRS	Cast brass Bullet	20w MR16 FL(BAB)	3.0 lbs.
DL-22-SS	Cast Stainless Steel Bullet	20w MR16 FL(BAB)	2.0 lbs.
DL-22-XEC-BLT	Cast aluminum Bullet, X-long collar	20w MR16 FL(BAB)	2.0 lbs.
DL-22-XEC-BRS	Cast brass Bullet, X-long collar	20w MR16 FL(BAB)	4.0 lbs.



**DL-22-BRS**  
mounted on  
FA-24-BRS



DL-22




DL-22-XEC



## MOUNTING ACCESSORIES

15" 381mm  
1.63" 41mm  
7.00" 178mm  
2" 51mm  
8.75" 222mm  
3" 76mm  
8.875" 225mm  
FA-03-RX/-BRS  
FA-03/BRS  
FA-03-LG  
FA-111-TREE (10"-41")  
FA-22-TREE (10"-41")  
FA-24-T10-BRS-BLT  
FA-111  
FA-24MD-CST-TREE (10"-41")  
FA-24/BRS  
FA-24-LG-SPUN / -BRS  
FA-24-LG-DH-SPUN / -BRS  
FA-24-LG-CST / -BRS  
FA-24-LG-DH-CST / -BRS  
FA-24-Strap-10  
FA-30-4  
FA-30-8  
FA-30-4  
FA-30-8  
FA-30  
FA-31  
FA-32  
FA-33  
FA-34  
-BRS = Brass Models (Arrow: couplers)  
STEM EXTENSIONS  
FA-01/BRS  
3" 76mm  
3" 76mm  
20" 508mm  
20" 508mm  
C/FA-25/BRS  
C/FA-26-75W/BRS  
2.65" 67mm  
13" 330mm  
FA-24-MD-CST-POST/-BRS  
3.25" 83mm  
0.875" 20mm  
3.25" 83mm  
0.875" 20mm  
5.25" 133mm  
5.25" 133mm  
FA-22-CST / -BRS  
FA-22-BRS  
FA-23-CST / -BRS  
FA-23-BRS  
2.65" 67mm  
1.4" 36mm  
2.65" 67mm  
1.4" 36mm  
FA-24-MD-CST-PC/-BRS  
FA-24-MD-CST/-BRS  
3" 76mm  
0.9" 23mm  
0.9" 23mm  
FA-24/BRS  
4.5" 114mm  
4.5" 114mm  
2.2" 51mm  
FA-YAD  
26" 660mm  
10" 254mm  
13" 330mm  
15" 381mm  
21" 533mm

## LIGHT DISTRIBUTIONS AND PHOTOMETRICS



## BEAM/GLARE CONTROL ACCESSORIES

- FA-08-21 Round 1/8" Hex Cell Louver
- FA-11-BLUE Blue Tempered Glass Lens
- FA-11-GREEN Green Tempered Glass Lens
- FA-98 Linear Spread Tempered Glass Lens
- FA-99 High Impact Clear Tempered Convex Glass
- FA-104 Wide Spread Tempered Glass Lens Softener

FSA-00

Powder Coat Finishes	Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Terra Cotta
Ordering Code	-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-TRC

## JOB INFORMATION

Type: \_\_\_\_\_ Date: \_\_\_\_\_

Job Name: \_\_\_\_\_

Cat. No.: \_\_\_\_\_

Lamp(s): \_\_\_\_\_

Specifier: \_\_\_\_\_

Contractor: \_\_\_\_\_

Notes: \_\_\_\_\_

**FOCUS INDUSTRIES INC.**  
25301 COMMERCENTRE DRIVE  
LAKE FOREST, CA 92630

**www.focusindustries.com**  
sales@focusindustries.com  
(949) 830-1350 • FAX (949) 830-3390