



# DIRECTIONAL LIGHTS DL-30-NL HID SERIES

**TYPE**

## SPECIFICATIONS

**CONSTRUCTION:** Cast aluminum or cast brass Bullet; matching heavy duty cast aluminum or brass adjustable swivel

**LENS:** High impact clear tempered convex glass

**LAMP SUPPLIED:** None (100w max); Use only outdoor rated PAR30 lamps

**SOCKET:** Medium base high temperature ceramic 600 volts, 660 watts 4 K.V. pulse rated. Brass nickel-plate screw shell with 150°C lead wires


**WIRING:** Standard 120 volt Black, White and Ground 9" lead wires

**MOUNTING:** None supplied. See Mounting Accessories below for options


**FINISH:** Aluminum-Black texture polyester powder coat; optional finishes available  
Brass-Unfinished brass; optional finishes available

**DOWN LIGHTS:** Add -D suffix to catalog number for down light without weep holes.

**NOTE:** Remote ballast required to correspond with PAR30 HID lamp to be used. Consult factory for Above Grade and Direct Burial ballast options.



DL-30-NL-EC-HID



DL-30-NL-AC-HID



**DOWN LIGHT  
APPLICATION  
AVAILABLE**



DL-30-NL-HID-BRS

**IP54**



## ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
DL-30-NL-ECHID-BLT	Cast aluminum HID PAR30 Bullet, extension collar	None	3.0 lbs.
DL-30-NL-ECHID-BRS	Cast brass HID PAR30 Bullet, extension collar	None	5.0 lbs.
DL-30-NL-ACHID-BLT	Cast aluminum HID PAR30 Bullet, angle collar	None	4.0 lbs.
DL-30-NL-ACHID-BRS	Cast brass HID PAR30 Bullet, angle collar	None	6.0 lbs.

## MOUNTING ACCESSORIES

C/FA-25/-26/BRS

C/FA-26-GFIC/BRS  
with covered receptacle

CFA-39/FA-39/BRS  
6' Cord and Plug

FA-22-CST / -BRS

FA-24-LG-CST / -BRS

FA-111

FA-24-MD-CST-PC/-BRS

FA-24-MD-CST/-BRS

FA-22-TREE  
(10"-41")

FA-111-TREE  
(10"-41")

FA-30 FA-31 FA-32 FA-33 FA-34  
-BRS = Brass Models (Arrow: couplers)  
**STEM EXTENSIONS**

## BEAM/GLARE CONTROL ACCESSORIES

FA-08-30	Round 1/4" Hex Cell Louver
FA-10-30-BLUE	Blue Tempered Glass Lens
FA-10-30-GREEN	Green Tempered Glass Lens
FA-40	Aluminum Extension Cap, Tempered Convex Glass Lens
FA-40-AC	Aluminum Angle Cap, Tempered Convex Glass Lens
FA-95	6" Extra-Long Extension Shield (aluminum only)
FA-98-30	Linear Spread Tempered Glass Lens
FA-104-30	Wide Spread Tempered Glass Lens Softener

## JOB INFORMATION

Type: \_\_\_\_\_ Date: \_\_\_\_\_

Job Name: \_\_\_\_\_

Cat. No.: \_\_\_\_\_

Lamp(s): \_\_\_\_\_

Specifier: \_\_\_\_\_

Contractor: \_\_\_\_\_

Notes: \_\_\_\_\_

**FOCUS INDUSTRIES INC.**  
25301 COMMERCENTRE DRIVE  
LAKE FOREST, CA 92630

www.focusindustries.com  
sales@focusindustries.com  
(949) 830-1350 • FAX (949) 830-3390

Powder Coat Finishes	Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Terra Cotta
Ordering Code	-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-TRC